

**SPECIFICATION**  
**Printing**

Printing method	9-Pin serial impact dot-matrix printing
Printing width	63.5mm
Column capacity	400 dots/line
Printing speed	4.5 line/s
Interface	Parallel/Serial/USB/Lan
Printing paper	75.5±0.5mm×φ80mm(max)
Line spacing	4.23mm (Adjustable by commands)
Character size	ANK, Font A: 1.6×3.1mm (9×9 dots) Font B: 1.2×3.1mm (7×9 dots) Chinese,traditional Chinese: 2.7×2.7mm (16×16 dots)
Column number	76mm paper: Font A - 32 columns /Font B - 42 columns / Chinese,traditional Chinese - 16 columns
<b>Character</b>	
Extension character sheet	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、PT151 (1251)
<b>Power</b>	
Power adaptor	Input : AC 110V/220V, 50~60Hz

Power source	Output : DC 24V/2.5A
Cash drawer output	DC 24V/1A
<b>Cutter</b>	
Auto cutter	Partial
<b>Physical characteristics</b>	
Gross weight	1.28KG
Dimensions	220×150×140mm (D×W×H)
<b>Environmental Requirements</b>	
Work environment	0~45°C, 10~80% RH
Storage environment	-10~60°C, 10~90% RH (no condensation)
<b>Reliability</b>	
Printer head life	10 Million Lines