



PARKING BOOM BARRIER

PROFESSIONAL MANUFACTURER

PARKING BARRIER

Simplified design, easy installation and maintenance reduces your labour cost

PROTECTION

Safety of Vehicle--- Boom Auto-reversing on Obstacle while on Photocell

MANUAL OPERATION:

Manually control in case of power failure

MODEL NAME	DZ602EG	DZ609EG
FRAMEWORK MATERIAL	Aluminium Alloy	Aluminium Alloy
DIMENSION	1020*340*260	980*310*260
REMOTE CONTROL	2* 433HZ (30MTR)	2* 433HZ (30MTR)
INPUT INTERFACE	Photocell, Loop Detector, Parking System, Wire Control	Photocell, Loop Detector, Parking System, Wire Control
MOTOR	100W – DC BRUSHLESS	100W – DC BRUSHLESS
POWER SUPPLY	DC24V	DC24V
INPUT	12V Relay Signal or Pulse wide	12V Relay Signal or Pulse wide
MCBF	3 million Time	3 million Time
OPENING / CLOSING TIME	3 SEC TO 6 SEC	3 SEC TO 6 SEC
BOOM	ALUMINUM ALLOY – 6M	ALUMINUM ALLOY – 6M
CHESIS THICKNESS	1.5MM	1.5MM
RELATIVE HUMIDITY	>90%	>90%
WORKING TEMPERATURE	-35 TO +80 DEGREE	-35 TO +80 DEGREE
POWER CONSUMPTION	80WATT	70WATT

DZ602EG



DZ609EG



10⁺ YEARS EXPERIENCE