

# Drying Tumbler

## Front Loading, Open Pocket



- + Stainless steel inner basket
- + Double walled glass wool insulated
- + Outer body duly painted, Electrically interlocked loading & unloading door,
- + No space required on sides of the machine.
- + Electrically controlled protection provided for auto timing, & auto reversing through micro controlled base cyclic timer / PLC
- + Auto digital temperature controls.
- + All controls front displayed with pilot lamps.
- + V-Belt and pulley drive for low torque and high speed.
- + Steam radiator/Electric Heaters : made out of coil and aluminum fins for steam heated, or fin type air heating elements for electrically heated machine.
- + Centrifugally balanced suction blower mounted directly on to the motor.
- + Electric. Steam, Gas or Thermic fluid heated type.



MODEL	CAPACITY DRY WEIGHT PER CHARGE	CYLINDER SIZE	DRIVE MOTOR	LOADING DOOR OPENING	EXHAUST DUCT SIZE	STEAM CONN.	LOAD	HEATING THERMIC FLUID CON.	DIESEL CONN.	GAS CONN.	DIM. WxDxH
		VOLUME	BLOWER MOTOR			CONSUM.		CONSUM.	CONSUM	CONSUM	
DT 15	15KG	800 X 600	0.75 KW	500	180 X 180	15 (0.5" BSP)	9/13.5 KW	15 (0.5" BSP)	6 (0.25" BSP)	6 (0.25" BSP)	900 X 1200 X 1780
		301L	0.75 KW			15KG/H		800KC/H	1.8L/H	1KG/H	
DT 30	30KG	950 X 850	0.75 KW	650	210 X 210	15 (0.5" BSP)	18/24 KW	15 (0.5" BSP)	6 (0.25" BSP)	6 (0.25" BSP)	1050 X 1500 X 1980
		602L	0.75 KW			30KG/H		1600KC/H	2.5L/H	2KG/H	
DT 60	60KG	1280 X 950	1.5 KW	800	300 X 300	15 (0.5" BSP)	36/48 KW	15 (0.5" BSP)	15 (0.5" BSP)	15 (0.5" BSP)	1380 X 1700 X 2380
		1221L	1.5 KW			60KG/H		3200KC/H	4L/H	4KG/H	
DT 120	120KG	1600 X 1200	2.25 KW	1000	300 X 300 2Nos	25 (1" BSP)	-	25 (1" BSP)	15 (0.5" BSP)	15 (0.5" BSP)	1760 X 2100 X 2990
		2441L	1.5 KW			120KG/H		6400KC/H	7.5L/H	8KG/H	
DT 240T FORWARD TILT MODEL	240KG	1800 X 1600	3.75 KW	1200	400 X 400 2Nos	25 (1" BSP)	-	25 (1" BSP)	15 (0.5" BSP)	15 (0.5" BSP)	1970 X 2600 X 3250
		4069L	2.2 KW			200KG/H		11000KC/H	11L/H	12KG/H	