

INDUSTRIAL HYDRO EXTRACTOR-DIRECT DRIVE

Inner basket outer basket all made of S.S Direct Drive with DC injection brake system. Fitted with specially designed buffer, noiseless vibration less operation. The SS drum is precisely balanced for safety & durability.

OPTIONAL :- Pneumatic door close system, VFD

CAPACITY	BASKET SIZE VOLUME	MOTOR	BASKET SPEED	DRAIN	OVERALL DIMENSIONS WXDxH
15 KG	550 x 300	2.25 KW	1000 RPM	2.5" BSP	800 x 1000 x 1050
	71 LTS				
25 KG	700 x 300	3.75 KW	1000 RPM	2.5" BSP	940 x 1140 x 1100
	115 LTS				
50 KG	1000 X 300	7.5 KW	750 RPM	3" BSP	1250 x 1550 x 1150
	235 LTS				



HYDRO EXTRACTOR 3 LEG SYSTEM

CAPACITY BASIS COTTON (KG.)	CAPACITY SIZE OX DEPTH(MM)	BASKET REVOLUTION (RPM)	CENTRIFUGAL EFFECT (%)	ELECTRIC POWER (HP)	DRAINAGE HOLE SIZE Ø (MM)
20	760 X 400	750	50-60	3	75
50	900 X 400	700	50-60	5	90
100	1220 X 400	700	50-60	10	100